

# WALL MOUNT ENCLOSURES



# **Product Summary**

TEXA NETWORK's Wall Mount Enclosures specially designed for small networking, domestic applications, Audio Video, Telecom and Lab applications. Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and powder coated with highest quality standards. Configuration for standard Enclosures are: Welded frame integrated with side walls and vented top cover with fan mounting provision, rear side of the Enclosure having wall mounting provision, front glass door with lock and Key provides the visibility and security. Wall Mount Enclosures are available in 4U to 15U Variants with 400mm/450mm/500mm/600mm depth. Width 550mm.





#### **Features**

- Conforms to DIN 41494 OR equivalent ISO Standards
- Adjustable 19" equipment mounting verticals provide better mounting flexibility and maximizes the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provide the best product quality and fastest delivery in the industry
- Top and bottom Panel with ventilation and cable entry facility
- Provision to mount cooling fans on the top panel
- Powder coated finish with pretreatment process meeting all industry standards
- Grounding and Bonding Options. 100% assured compatibility with all equipment conforming to DIN 41494 (General industrial standard for equipment)

#### **Technical Data**

Rack Standard : Conforms to DIN 41494 or equivalent standard

Construction : Welded

Front Door : Lockable Toughened Glass Door

Basic Frame : Steel

Equipment Mounting : DIN Standard Slots

Mounting Angle : 19" Mounting angles made of formed steel

Standard Finish : Powder Coated

Top and Bottom Cover : Welded to Frame, Vented and Field Cable entry exit cut outs

Standard Color : Grey

Static Load : 25 kgs





### **Part Code & Dimensions**

Part Code	Height OD In mm(H)	Height Usable in mm (H)	Height Usable in U (H)	Width In mm(W)	Usable Width(W)	Depth In mm(D)	Usable In mm(D)
TNC4U-5040BLK	258	178	04U	550	19"	400	350
TNC6U-5045BLK	347	267	06U	550	19"	450	400
TNC9U-5045BLK	480	400	09U	550	19"	450	400
TNC12U-5045BLK	613	533	<b>12</b> U	550	19"	450	400
TNC15U-5045BLK	747	667	<b>15</b> U	550	19"	450	400
TNC4U-5550BLK	258	178	04U	550	19"	500	450
TNC6U-5550BLK	347	267	06U	550	19"	500	450
TNC9U-5550BLK	480	400	09U	550	19"	500	450
TNC12U-5550BLK	613	533	12U	550	19"	500	450
TNC15U-5550BLK	747	667	<b>15</b> U	550	19"	500	450
TNC4U-5560BLK	258	178	04U	550	19"	600	550
TNC6U-5560BLK	347	267	06U	550	19"	600	550
TNC9U-5560BLK	480	400	09U	550	19"	600	550
TNC12U-5560BLK	613	533	12U	550	19"	600	550
TNC15U-5560BLK	747	667	<b>15</b> U	550	19"	600	550

## **Features**

- Power Distribution Units.
- 1U Horizontal Cable Manager.
- Fan (Not in 4U)
- Hardware Packet

# **Orderable Accessories**

- Cantilever Tray
- 2U Horizontal Cable Manager
- Hardware Packet