

19-port Full Gigabit PoE Fiber Switch

(TN319PG)



OVERVIEW

The TN319PG is an unmanaged gigabit PoE fiber switch. It has 18*10/100/1000Base-T RJ45 ports and 1*1000Base-X uplink SFP fiber port. Port 1-16 can support PoE+ power supply and single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and recognize the power-receiving equipment that meets the standard and supply power through the network cable. It can supply power to PoE terminal equipment such as wireless AP, IP camera, VoIP phone, video access control intercom, etc. through a network cable to meet the network environment that needs a high-density PoE power supply. It is suitable for hotels, campuses, factory quarters, and small and medium-sized enterprises to form an economy efficient network. Unmanaged mode, plug and play, no configuration, easy to use.

FEATURE

Full gigabit rate, optical port uplink

- Support non-blocking wire-speed forwarding for smoother transmission.
- Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- Provides Gigabit Ethernet ports and SFP port uplink for flexible networking and meets the networking requirements of various scenarios.

Smart PoE power supply

- 16*10/100/1000Base-T RJ45 ports support PoE power to meet the needs of PoE power in various scenarios in the security field.
- Comply with PoE+ power supply, automatically identify PoE devices for power without Damaging non-PoE devices, and the single port max PoE output power is 30W.
- PoE port supports the watchdog function, which automatically detects the data communication status in real-time. When the port communication fails, the corresponding port PoE will automatically restart and repair the network communication by itself.

Stable and reliable, easy to use

- CCC, CE, FCC, RoHS.
- Plug and play, no configuration, and convenient.
- The user-friendly panel can show the device status through the LED indicator of PWR, Link, and PoE.
- Self-developed power supply, high redundancy design, providing a long-term and Stable PoE power output.
- Low power consumption, no fan, galvanized steel casing, excellent heat dissipation to ensure the stable operation of the switch.

Innovative function

- PoE watchdog: The watchdog function is enabled by default for ports 1-16, which can automatically detect the data communication status in real-time. When the port communication fails, the corresponding port POE will automatically restart, and the network communication can be repaired by itself, eliminating manual maintenance costs.
- Long-distance and VLAN mode (250m): switch to ON position (default off), the port 9-16 rate is 10M, and the physical VLAN isolation function is turned on at the same time to suppress broadcast storms and improve network performance. Using the existing twisted pair can break through the 100 meters transmission limit, and the transmission distance can be up to 250 meters. At the same time, it can solve the problem of poor transmission caused by aging lines.

TECHNICAL SPECIFICATION

Model	TN319PG	TN319PG - 250
Interface Characteristics		
Fixed Port	1*1000Base-X uplink SFP fiber port (Data) 2*10/100/1000Base-T uplink RJ45 ports (Data) 16*10/100/1000Base-T PoE ports (Data/Power)	
Ethernet Port	Port 1-18 can support 100/1000Base-T(X) auto-sensing, full/half duplex MDI/ MDI-X self-adaption	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤ 250 meters) 100BASE-TX: Cat5 or later UTP (≤ 100 meters) 1000BASE-T: Cat5e or later UTP (≤ 100 meters)	
Optical Fiber Port	Gigabit optical fiber port, default no include optical module (optional single-mode/ multi-mode, single fiber/ dual fiber optical module. LC)	
Optical Cable/ Distance	Multi-mode: 850nm/ 0-550m Single-mode: 1310nm/ 0-40km, 1550nm/ 0-120km	
Functional Switch	250m: long-distance function (Default off, Use:on), After opening, port 9-16 support 10M/250m transmission and PoE watchdog function	
Chip Parameter		
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x	
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	38Gbps (Non-blocking)	
Forwarding Rate@64byte	28.27Mpps	
MAC	4K	
Buffer Memory	4M	
Jumbo Frame	9.2K	
LED Indicator	Power: PWR (Green), Network: Link (Green) PoE: PoE (Red), Functional switch: 100m/250m (Green)	

TECHNICAL SPECIFICATION

PoE & Power Supply		
PoE Port	Port 1-16	
Power Supply	1/2(+) 3/6(-)	
Pin		
Max Power Per Port	30W, PoE+	
Total PWR / Input Voltage	160W/ (AC100-240V)	250W/ (AC100-240V)
Power Consumption	Standby <5W, Full load <160W	Standby <5W, Full load <250W
Distance Power Supply	Built-in power supply, AC100~240V 50-60Hz, 3.0A	
Physical Parameter		
Operation TEMP/ Humidity	-20~+55°C, 5%~90% RH Non condensing	
Storage TEMP/ Humidity	-40~+80°C, 5%~95% RH Non condensing	
Dimension (L*W*H)	350*215*44mm	
Net /Gross Weight	1.75kg / 2.25kg	2.0kg / 2.5kg
Installation	Desktop, Rack mounted	
Certification & Warranty		
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30	
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS	
Warranty	1 year	