

36-port 10G Uplink L3 Managed Ethernet Fiber Switch

(TN3M36P10GCSW)



OVERVIEW

The TN3M36P10GCSW is a 10G uplink L3 managed Ethernet fiber switch independently developed by ONV. It has 8*10/100/1000Base-T RJ45 or 8*100/1000Base-X SFP (combo ports) and 16*100/1000Base-X SFP ports and 4*1/10G SFP+ fiber slot ports. Each port can support wire-speed forwarding.

The TN3M36P10GCSW has L3 full network management function, supports IPV4/ IPV6 management, dynamic routing and forwarding, complete security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS(<20ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode. It satisfies high-density network application environment and is suitable for medium, large-scale scenes such as hotel, campus, park, shopping mall, scenic spot, hospital, bank to form an economical, efficient

FEATURE

Gigabit multi fiber port access, 10G SFP+ fiber port uplink

- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- Supports Gigabit Ethernet port and gigabit.SFP fiber slot port and 1/10G SFP+ fiber slot port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

Strong business processing capability

- ERPS/STP/RSTP/MSTP.
- Static and dynamic aggregation.
- IGMP V1/V2 and IGMP Snooping.
- IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN, and QinQ configuration.
- QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

Security

- 802.1X authentication.
- Port isolation, Storm control.
- Port+MAC binding, IP+MAC+port binding.

Stable and reliable

- CC, CE, FCC, RoHS.
- Low power consumption, galvanized steel casing, with fan.
- Self-developed power supply high redundancy design, providing a long term and stable power output.
- The user-friendly panel can show the device status through the LED indicator of PWR, Link.

Easy operation and maintenance management

- HTTPS, SSLV3, and SSHV1/V2.
- RMON, system log, LLDP, and port traffic statistics.
- CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

TECHNICAL SPECIFICATION

Model	TN3M36P10GCSW
Interface Characteristics	
Fixed Port	1*AC100-240V input port 1*Console RS232 port (115200,N,8,1) 4*1/10G SFP+ fiber slot ports (Data) 16*100/1000Base-X SFP ports (Data) 8*10/100/1000Base-T RJ45 or 8*100/1000Base-X SFP combo port (Data)
Ethernet Port	Port 1-8 support 10/100/1000Base-T(X) auto-sensing, full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e/6 or later UTP(≤100 meters)
Optical Fiber Port	Gigabit SFP optical fiber port and 10G SFP+ optical fiber port, default no include optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Fiber Port Expansion	Support Turbo overclocking 2.5G optical module expansion and ring network
Optical Cable/Distance	Multi-mode: 850nm//0-500M(1G), 850nm/0-300M (10G) Single-mode:1310nm/ 0-40KM, 1550nm/ 0-120KM.
Chip Parameter	
Network Management Type	L3
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-LR/SR, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	336Gbps