

## 52-port 10G Uplink L3 Managed PoE Fiber Switch

(TN3M52P4TPOESW)

AC100~240V 50-60Hz 6.6A



## OVERVIEW

The TN3M52P4TPOESW is a 10G uplink L3 managed PoE fiber switch. It has 48\*10/100/1000Base-T RJ45 ports and 4\*1/10G SFP+ fiber slot ports. Port 1-48 can support IEEE802.3af/at PoE standard. Single-port PoE power reaches 30W. As a PoE power supply device, it can automatically detect and recognize the power receiving equipment that meets the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP phone, building visual access control intercom, etc. through network cable, to meet the network environment that needs high-density PoE power supply. It is suitable for hotel, campus, factory dormitory and small and medium-sized enterprise.

The TN3M52P4TPOESW has L3 full network management function, supports IPV4/ IPV6 management, dynamic route full-speed forwarding, complete security protection mechanism, complete ACL/ QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application

requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

## FEATURE

### Gigabit wire speed access, 10G uplink

- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- Support Gigabit Ethernet port and 10G SFP+ uplink port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

### Intelligent PoE power supply

- IEEE802.3af/at PoE standard, without damaging non-PoE devices.
- PoE network management, realize PoE port power allocation, priority setting, port power status viewing, time scheduling, etc.
- 48\*10/100/1000Base-T RJ45 ports can support POE power supply to meet the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.

**Security**

- 802.1X authentication.
- Port isolation, Storm control.
- IP-MAC-VLAN-Port binding.

**Strong business processing capability**

- ERPS/STP/RSTP/MSTP.
- Static and dynamic aggregation.
- IGMP V1/V2 and IGMP Snooping.
- IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN, and QinQ configuration.
- QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

**Stable and reliable**

- CCC, CE, FCC, RoHS.
- Low power consumption, with fan, galvanized steel casing.
- The user-friendly panel can show the device status through the LED indicator of PWR, Link, PoE.
- Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.

**Easy operation and maintenance management**

- HTTPS, SSLV3, and SSHV1/V2.
- RMON, system log, LLDP, and port traffic statistics.
- CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

**TECHNICAL SPECIFICATION**

Model	TN3M4P4TPOESW
Interface Characteristics	
Fixed Port	1*Console RS232 port (115200,N,8,1) 4*1/10G uplink SFP+ fiber slot ports (Data) 48*10/100/1000Base-T PoE ports (Data/Power)
Ethernet Port	Port 1-48 can support 10/100/1000BaseT auto-sensing, Full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e/6 or later UTP(≤100 meters)
Optical Fiber Port	Gigabit SFP optical fiber port and 10G SFP+ optical fiber port, default no include optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)

Optical Fiber Port Expansion	Support Turbo overclocking 2.5G optical module expansion and ing network
Optical Cable/Distance	Multi-mode:850nm/ 0-500M(1G), 850nm/0-300M (10G), Single-mode:1310nm/ 0-40KM, 1550nm/ 0-120KM.
Chip Parameter	
Network Management Type	L3
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-LR/SR, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	368Gbps (non-blocking)
Forwarding Rate@64byte	131Mpps
CPU	Dual core 1GHz
DRAM	2GB

FLASH	256MB
MAC	32K
Buffer	16MB
Jumbo Frame	12KB
Memory LED Indicator	System: SYS (Green), Network:Link(Yellow), PoE: PoE (Green), Fiber port: L/A (Green)
Reset Switch	Yes, press and hold the switch for 10 seconds and release it to restore the factory settings
PoE & Power Supply	
PoE Port	Port 1 to 48
PoE Management	PoE working status display, Port PoE on/off, af/at power distribution
Power Supply Pin	1/2 (+) 3/6(-)
Max Power Per Port	30W, IEEE802.3af/at
Power Consumption	Standby<30W, Full Load<600W
Power Supply	Built-in power supply, AC100~240V 50-60Hz 6.6A
Physical Parameter	
Operation TEMP/ Humidity	20~+55°C, 5%~90% RH Non condensing

Storage TEMP/ Humidity	-40~ +80°C, 5%~95% RH Non condensing
Dimension (L*W*H)	440*290*44.5mm
Net /Gross Weight	<4.8kg / <5.5kg
Installation	Desktop, 19 inch 1U cabinet installation
Certification & Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
Warranty	3 years, lifelong maintenance.